


## XR2000 IP-PBX Data Sheet

The XR2000 is an Intel-Celeron® based Asterisk® IP PBX with PSTN / telephone ports. The XR2000 features Elastix™ Asterisk distribution with up to 32 analog ports, up to eight BRI ISDN ports, and/or a single PRI/R2/CAS ISDN E1/T1 port. The XR2000 supports up to 160 PSTN / Analog phones ports with external Astribank units, up to 200 users and up to 45 concurrent calls.



[To see the different XR2000 configurations on our Web site click here.](#)

### Features

- User friendly Web Interface
- Interface in Different Languages
- CDR (Call Details Record) via Web access
- TDM/SIP/IAX Trunks
- Remote Extensions
- Voicemail
- Fax Support
- Voicemail to Email
- IVR Menu System
- Ring Groups
- Call Queues
- Conference Rooms
- Follow-Me
- Time-Based Routing
- Advanced Dialing Rules
- Music-On-Hold
- Paging and Intercom
- Web Access to Voicemail
- Admin Status Screen
- Package Manager (for easy updates)
- Network Settings Tool
- Phone Provisioning Tool
- Echo Cancellation - OSLEC (Open Source Line Echo Cancelation)


### Software

<b>Asterisk version</b>	1.4x/1.6x (Elastix)
<b>Linux version</b>	CentOS 5.x
<b>GUI</b>	FreePBX
<b><u>Rapid Tunneling™</u></b>	Utility providing secure remote access for product support purposes
<b><u>TwinStar™</u></b> (optional)	High availability solution for complete Asterisk-based systems (requires two identical base units and an <a href="#">Astribank</a> device).

## Hardware

Processor	Intel Celeron 1.2 GHz
RAM	1 GB
Hard disk	From 250GB 2.5" (500GB optional)
<a href="#">Echo Cancellation Module</a>	Voice enhancement & echo cancellation (optional)
USB	2 external USB 2.0
<a href="#">I/O Ports</a> (model-specific)	Input/Output ports for Asterisk peripheral device support
<a href="#">Rapid PA™</a> (optional and model-specific)	Public Address capability for FXS port(s)


## Telephony

Maximum number of concurrent calls	45
Maximum number of built-in analog ports	32 (additional ports with external Astribank units)
Number of E1 / T1 ports	1 (up to 30 concurrent PRI/R2/CAS calls)
Maximum telephony modules supported internally	4 (additional Astribank ports are supported by adding Astribank units)
Maximum number of telephony ports supported internally	54 (E1 PRI/R2/CAS + 24 analog ports)
<a href="#">Supported Xorcom telephony modules</a>  <i>Elastix Hardware Certified</i>	<ul style="list-style-type: none"> <li>• 8 FXS ports</li> <li>• 8 FXS ports + I/O ports</li> <li>• 8 FXO ports</li> <li>• 2 FXO ports, 6 FXS ports + I/O ports</li> <li>• 1 PRI/R2/CAS port</li> <li>• Up to 8 BRI ISDN ports</li> </ul>

## Network

Ethernet port	10/100 Mb/s
---------------	-------------

## Power

Power supply	Internal
Voltage	Switching, auto adjust 110/220 Volts, 50/60 Hz
Power consumption	230 Watts (maximum)
Built in grounding connection	

## Maintenance and Support

- Monitor and keyboard support
- [Rapid Recovery™](#) backup utility provided on disk-on-key (optional)
- [Rapid Tunneling™](#) utility providing secure remote access for product support purposes
- Internet updates

## Environment

Storage temperature	-20° to 70° Celsius (-4° -158° F)
Working temperature	0° to 40° Celsius (32° -104° F)
Humidity	20%-95%, non condensing

## Dimensions and Weight

Weight	8 Kg 18Lbs (weight depends on configuration)
Size	19" 2U industry standard rack-mountable chassis

*Specifications may change without prior notice.*



Mayorista de Valor Agregado  
en México

Av. División del Norte 1354-202, Col. Letrán Valle  
Distrito Federal, México, 03650

T: + 52 (55) 8590 9000

E: [ventas@neocenter.com](mailto:ventas@neocenter.com) W: [www.neocenter.com](http://www.neocenter.com)