- High definition Dolby® Digital Plus enhanced sound
- Unrivaled durability plug it in and go
- In-line controls to easily manage calls and tracks





Headset type On-ear Cable length 1200 mm (47.2 in) Connector 4-pole Compatibility Most devices with 3.5 mm Jack connector (0.14 in) Weight 226 g 8 oz) Dimensions, main unit L 178 x W 160 mm (7 x 6.3 in) Speaker size 40 mm Speaker sensitivity 119 dB at 11/J1kHz THD (Total Harmonic Distortion) <5%@TkHz Speaker impedance 32 ohm Speaker frequency range 20Hz- 20kHz Microphone type Omni directional Microphone frequency range 100Hz – 8kHz Microphone sensitivity -10° c to 55° C (14 F to 131 F) Storage temperature -10° C to 55° C (40 F to 149 F) Reliability testing Drop tested from 2 m height, fold tested 3500 times, bend tested 10000 times, cable tested to withstand 15 kg pull force, dirt, temperature and humidity tested Jabra Revo materials Silicon, PCM, PC, Zinc, AL, PU, ABS, TPE Features Foldable design, detachable 3.5 mm audio cable (1.2 m), 1 quick start guide, 1 Jabra Sevon headphones, 1 protective bag, 1 detachable 3.5 mm audio cable (1.2 m), 1 quick start guide, 1 Jabra Sevon headphones, 1 protective bag, 1 detachable 3.5 mm audio cable (1.2 m), 1 quick start guide, 1 Jabra Sound App unique registration leaflet, 1 warranty	FEATURE	BENEFIT
Wearing style On-ear Cable length 1200 mm (47.2 in) Connector 4-pole Compatibility Most devices with 3.5 mm Jack connector (0.14 in) Weight 226 g (8 oz) Dimensions, main unit L 178 x W 160 mm (7 x 6.3 in) Speaker size 40 mm Speaker sensitivity 119 dB at 1V/1kHz THD (Total Harmonic Distortion) <5%@TKHz Speaker impedance 32 ohm Speaker max input power 30mW music Speaker frequency range 20Hz- 20kHz Microphone type Omni directional Microphone frequency range 100Hz - 8kHz Microphone sensitivity -42 dB Operating temperature -10° C to 55° C (14 F to 131 F) Storage temperature 40° C to 65° C (-40 F to 149 F) Reliability testing Drop tested from 2 m height, fold tested 3500 times, bend tested 10000 times, cable tested to withstand 15 kg pull force, dirt, temperature and humidity tested Jabra Revo materials Silicon, PCM, PC, Zinc, AL, PU, ABS, TPE Features Foldable design, detachable 3.5 mm cable, dual 3.5 mm jack connectors for right or left side use and sharing music, in-line controls for music and calls: answer/end call*, reject call*, voice dialing*, last number redial*, volume control**, track control*, play/pause music* What's in the box? 1 Jabra Revo headphones, 1 protective bag, 1 detachable 3.5 mm audio cable (1.2 m), 1 quick start guide, 1 Jabra Sound App unique registration leaflet, 1 warranty leaflet, 1 register paper. Certification CE	Headset type	Corded stereo on-ear headphones
Cable length 1200 mm (47.2 in) Connector 4-pole Compatibility Most devices with 3.5 mm Jack connector (0.14 in) Weight 226 g (8 oz) Dimensions, main unit L 178 x W 160 mm (7 x 6.3 in) Speaker size 40 mm Speaker sensitivity 119 dB at 1V/1kHz THD (Total Harmonic Distortion) <5%@1KHz Speaker impedance 32 ohm Speaker simpedance 32 ohm Speaker frequency range 20Hz- 20kHz Microphone type Omni directional Microphone frequency range 100Hz - 8kHz Microphone sensitivity -42 dB Operating temperature -10° C to 55° C (14 F to 131 F) Storage temperature -40° C to 65° C (-40 F to 149 F) Reliability testing Drop tested from 2 m height, fold tested 3500 times, bend tested 10000 times, cable tested to withstand 15 kg pull force, dirt, temperature and humidity tested Jabra Revo materials Silicon, PCM, PC, Zinc, AL, PU, ABS, TPE Features Foldable design, detachable 3.5 mm cable, dual 3.5 mm jack connectors for right or left side use and sharing music, In-line controls for music and calls: answer/end call*, reject call*, voice dialing*, last number redial*, volume control**, track control*, play/pause music* What's in the box? 1 Jabra Revo headphones, 1 protective bag, 1 detachable 3.5 mm audio cable (1.2 m), 1 quick start guide, 1 Jabra Sound App unique registration leaflet, 1 warranty leaflet, 1 register paper. Certification CE		·
Connector 4-pole Compatibility Most devices with 3.5 mm Jack connector (0.14 in) Weight 226 g (8 oz) Dimensions, main unit L 178 x W 160 mm (7 x 6.3 in) Speaker size 40 mm Speaker sensitivity 119 dB at 1V/1kHz THD (Total Harmonic Distortion) 5-5%@1KHz Speaker impedance 32 ohm Speaker max input power 30mW music Speaker frequency range 20Hz- 20kHz Microphone type 0mni directional Microphone frequency range 100Hz - 8kHz Microphone sensitivity -42 dB Operating temperature -10° C to 55° C (14 F to 131 F) Storage temperature -40° C to 65° C (-40 F to 149 F) Reliability testing Drop tested from 2 m height, fold tested 3500 times, bend tested 10000 times, cable tested to withstand 15 kg pull force, dirt, temperature and humidity tested Jabra Revo materials Silicon, PCM, PC, Zinc, AL, PU, ABS, TPE Features Foldable design, detachable 3.5 mm cable, dual 3.5 mm jack connectors for right or left side use and sharing music, In-line controls for music and calls: answer/end call*, reject call*, voice dialing*, last number redial*, volume control**, track control*, play/pause music* What's in the box? 1 Jabra Revo headphones, 1 protective bag, 1 detachable 3.5 mm audio cable (1.2 m), 1 quick start guide, 1 Jabra Sound App unique registration leaflet, 1 warranty leaflet, 1 register paper. Certification CE		1200 mm (47.2 in)
Weight 226 g (8 oz) Dimensions, main unit L 178 x W 160 mm (7 x 6.3 in) Speaker size 40 mm Speaker sensitivity 119 dB at 1V/1kHz THD (Total Harmonic Distortion) <5%@TKHz Speaker impedance 32 ohm Speaker frequency range 30mW music Speaker frequency range 20Hz- 20kHz Microphone type 0mni directional Microphone frequency range 100Hz - 8kHz Microphone sensitivity -42 dB Operating temperature -10° C to 55° C (14 F to 131 F) Storage temperature -40° C to 65° C (-40 F to 149 F) Reliability testing Drop tested from 2 m height, fold tested 3500 times, bend tested 10000 times, cable tested to withstand 15 kg pull force, dirt, temperature and humidity tested Jabra Revo materials Silicon, PCM, PC, Zinc, AL, PU, ABS, TPE Features Foldable design, detarhable 3.5 mm cable, dual 3.5 mm jack connectors for right or left side use and sharing music, In-line controls for music and calls: answer/end call*, reject call*, voice dialing*, last number redial*, volume control**, track control**, play/pause music* What's in the box? 1 Jabra Sound App unique registration leaflet, 1 warranty leaflet, 1 register paper. Certification CE	Connector	•
Dimensions, main unit L 178 x W 160 mm (7 x 6.3 in) Speaker size 40 mm Speaker sensitivity 119 dB at 1V/1kHz THD (Total Harmonic Distortion) 55%@1KHz Speaker impedance 32 ohm Speaker frequency range 20Hz- 20kHz Microphone type Omni directional Microphone frequency range 100Hz - 8kHz Microphone sensitivity -42 dB Operating temperature -10° C to 55° C (14 F to 131 F) Storage temperature -40° C to 65° C (-40 F to 149 F) Reliability testing Drop tested from 2 m height, fold tested 3500 times, bend tested 10000 times, cable tested to withstand 15 kg pull force, dirt, temperature and humidity tested Jabra Revo materials Silicon, PCM, PC, Zinc, AL, PU, ABS, TPE Features What's in the box? University 1 pairs as well as sound app unique registration leaflet, 1 warranty leaflet, 2 warranty leaflet	Compatibility	Most devices with 3.5 mm Jack connector (0.14 in)
Speaker size 40 mm Speaker sensitivity 119 dB at 1V/1kHz THD (Total Harmonic Distortion) <5%@1KHz Speaker impedance 32 ohm Speaker max input power 30mW music Speaker frequency range 20Hz- 20kHz Microphone type 0mni directional Microphone frequency range 100Hz - 8kHz Microphone sensitivity -42 dB Operating temperature -10° C to 55° C (14 F to 131 F) Storage temperature -40° C to 65° C (-40 F to 149 F) Reliability testing 0rop tested from 2 m height, fold tested 3500 times, bend tested 10000 times, cable tested to withstand 15 kg pull force, dirt, temperature and humidity tested Jabra Revo materials Silicon, PCM, PC, Zinc, AL, PU, ABS, TPE Features Foldable design, detachable 3.5 mm cable, dual 3.5 mm jack connectors for right or left side use and sharring music, In-line controls for music and calls: answer/end call*, reject call*, voice dialing*, last number redial*, volume control**, track control*, play/pause music* What's in the box? 1 Jabra Sound App unique registration leaflet, 1 warranty leaflet, 1 register paper. Certification CE	Weight	226 g (8 oz)
Speaker sensitivity THD (Total Harmonic Distortion) Speaker impedance Speaker max input power Speaker frequency range 20Hz- 20kHz Microphone type Omni directional Microphone frequency range Microphone sensitivity -42 dB Operating temperature -10° C to 55° C (14 F to 131 F) Storage temperature Reliability testing Drop tested from 2 m height, fold tested 3500 times, bend tested 10000 times, cable tested to withstand 15 kg pull force, dirt, temperature and humidity tested Jabra Revo materials Features Foldable design, detachable 3.5 mm cable, dual 3.5 mm jack connectors for right or left side use and sharing music, In-line controls for music and calls: answer/end call*, reject call*, voice dialing*, last number redial*, volume control**, track control*, play/pause music* What's in the box? Lettification The dat 11/1kHz 119 dB at 11/1kHz 50m(1KHz 20m(1KHz 40m(1KHz 40m(Dimensions, main unit	L 178 x W 160 mm (7 x 6.3 in)
THD (Total Harmonic Distortion) 5%@IKHz Speaker impedance 32 ohm Speaker max input power 30mW music Speaker frequency range 20Hz- 20kHz Microphone type Omni directional Microphone frequency range 100Hz - 8kHz Microphone sensitivity -42 dB Operating temperature -10° C to 55° C (14 F to 131 F) Storage temperature -40° C to 65° C (-40 F to 149 F) Reliability testing Drop tested from 2 m height, fold tested 3500 times, bend tested 10000 times, cable tested to withstand 15 kg pull force, dirt, temperature and humidity tested Jabra Revo materials Silicon, PCM, PC, Zinc, AL, PU, ABS, TPE Features Foldable design, detachable 3.5 mm cable, dual 3.5 mm jack connectors for right or left side use and sharing music, In-line controls for music and calls: answer/end call*, reject call*, voice dialing*, last number redial*, volume control**, track control*, play/pause music* What's in the box? 1 Jabra Revo headphones, 1 protective bag, 1 detachable 3.5 mm audio cable (1.2 m), 1 quick start guide, 1 Jabra Sound App unique registration leaflet, 1 warranty leaflet, 1 register paper. Certification CE	Speaker size	40 mm
Speaker impedance32 ohmSpeaker max input power30mW musicSpeaker frequency range20Hz- 20kHzMicrophone type0mni directionalMicrophone frequency range100Hz - 8kHzMicrophone sensitivity-42 dBOperating temperature-10° C to 55° C (14 F to 131 F)Storage temperature-40° C to 65° C (-40 F to 149 F)Reliability testingDrop tested from 2 m height, fold tested 3500 times, bend tested 10000 times, cable tested to withstand 15 kg pull force, dirt, temperature and humidity testedJabra Revo materialsSilicon, PCM, PC, Zinc, AL, PU, ABS, TPEFeaturesFoldable design, detachable 3.5 mm cable, dual 3.5 mm jack connectors for right or left side use and sharing music, In-line controls for music and calls: answer/end call*, reject call*, voice dialing*, last number redial*, volume control**, track control*, play/pause music*What's in the box?1 Jabra Revo headphones, 1 protective bag, 1 detachable 3.5 mm audio cable (1.2 m), 1 quick start guide, 1 Jabra Sound App unique registration leaflet, 1 warranty leaflet, 1 register paper.CertificationCE	Speaker sensitivity	119 dB at 1V/1kHz
Speaker max input power Speaker frequency range 20Hz- 20kHz Microphone type Omni directional Microphone frequency range 100Hz - 8kHz Microphone sensitivity -42 dB Operating temperature -10° C to 55° C (14 F to 131 F) Storage temperature -40° C to 65° C (-40 F to 149 F) Reliability testing Drop tested from 2 m height, fold tested 3500 times, bend tested 10000 times, cable tested to withstand 15 kg pull force, dirt, temperature and humidity tested Jabra Revo materials Silicon, PCM, PC, Zinc, AL, PU, ABS, TPE Features Foldable design, detachable 3.5 mm cable, dual 3.5 mm jack connectors for right or left side use and sharing music, In-line controls for music and calls: answer/end call*, reject call*, voice dialing*, last number redial*, volume control**, track control*, play/pause music* What's in the box? 1 Jabra Revo headphones, 1 protective bag, 1 detachable 3.5 mm audio cable (1.2 m), 1 quick start guide, 1 Jabra Sound App unique registration leaflet, 1 warranty leaflet, 1 register paper. Certification CE	THD (Total Harmonic Distortion)	<5%@1KHz
Microphone type Microphone frequency range Microphone frequency range Microphone frequency range Microphone sensitivity -42 dB Operating temperature -10° C to 55° C (14 F to 131 F) Storage temperature -40° C to 65° C (-40 F to 149 F) Reliability testing Drop tested from 2 m height, fold tested 3500 times, bend tested 10000 times, cable tested to withstand 15 kg pull force, dirt, temperature and humidity tested Jabra Revo materials Silicon, PCM, PC, Zinc, AL, PU, ABS, TPE Features Foldable design, detachable 3.5 mm cable, dual 3.5 mm jack connectors for right or left side use and sharing music, In-line controls for music and calls: answer/end call*, reject call*, voice dialing*, last number redial*, volume control**, track control*, play/pause music* What's in the box? 1 Jabra Revo headphones, 1 protective bag, 1 detachable 3.5 mm audio cable (1.2 m), 1 quick start guide, 1 Jabra Sound App unique registration leaflet, 1 warranty leaflet, 1 register paper. Certification CE	Speaker impedance	32 ohm
Microphone type Omni directional Microphone frequency range 100Hz - 8kHz Microphone sensitivity -42 dB Operating temperature -10° C to 55° C (14 F to 131 F) Storage temperature -40° C to 65° C (-40 F to 149 F) Reliability testing Drop tested from 2 m height, fold tested 3500 times, bend tested 10000 times, cable tested to withstand 15 kg pull force, dirt, temperature and humidity tested Jabra Revo materials Silicon, PCM, PC, Zinc, AL, PU, ABS, TPE Features Foldable design, detachable 3.5 mm cable, dual 3.5 mm jack connectors for right or left side use and sharing music, In-line controls for music and calls: answer/end call*, reject call*, voice dialing*, last number redial*, volume control**, track control*, play/pause music* What's in the box? 1 Jabra Revo headphones, 1 protective bag, 1 detachable 3.5 mm audio cable (1.2 m), 1 quick start guide, 1 Jabra Sound App unique registration leaflet, 1 warranty leaflet, 1 register paper. Certification CE	Speaker max input power	30mW music
Microphone frequency range Microphone sensitivity -42 dB Operating temperature -10° C to 55° C (14 F to 131 F) Storage temperature -40° C to 65° C (-40 F to 149 F) Reliability testing Drop tested from 2 m height, fold tested 3500 times, bend tested 10000 times, cable tested to withstand 15 kg pull force, dirt, temperature and humidity tested Jabra Revo materials Silicon, PCM, PC, Zinc, AL, PU, ABS, TPE Features Foldable design, detachable 3.5 mm cable, dual 3.5 mm jack connectors for right or left side use and sharing music, In-line controls for music and calls: answer/end call*, reject call*, voice dialing*, last number redial*, volume control**, track control*, play/pause music* Uhat's in the box? 1 Jabra Revo headphones, 1 protective bag, 1 detachable 3.5 mm audio cable (1.2 m), 1 quick start guide, 1 Jabra Sound App unique registration leaflet, 1 warranty leaflet, 1 register paper. Certification CE	Speaker frequency range	20Hz- 20kHz
Microphone sensitivity Operating temperature -10° C to 55° C (14 F to 131 F) Storage temperature -40° C to 65° C (-40 F to 149 F) Reliability testing Drop tested from 2 m height, fold tested 3500 times, bend tested 10000 times, cable tested to withstand 15 kg pull force, dirt, temperature and humidity tested Jabra Revo materials Silicon, PCM, PC, Zinc, AL, PU, ABS, TPE Features Foldable design, detachable 3.5 mm cable, dual 3.5 mm jack connectors for right or left side use and sharing music, In-line controls for music and calls: answer/end call*, reject call*, voice dialing*, last number redial*, volume control**, track control*, play/pause music* What's in the box? 1 Jabra Revo headphones, 1 protective bag, 1 detachable 3.5 mm audio cable (1.2 m), 1 quick start guide, 1 Jabra Sound App unique registration leaflet, 1 warranty leaflet, 1 register paper. Certification CE	Microphone type	Omni directional
Operating temperature -10° C to 55° C (14 F to 131 F) Storage temperature -40° C to 65° C (-40 F to 149 F) Reliability testing Drop tested from 2 m height, fold tested 3500 times, bend tested 10000 times, cable tested to withstand 15 kg pull force, dirt, temperature and humidity tested Silicon, PCM, PC, Zinc, AL, PU, ABS, TPE Features Foldable design, detachable 3.5 mm cable, dual 3.5 mm jack connectors for right or left side use and sharing music, In-line controls for music and calls: answer/end call*, reject call*, voice dialing*, last number redial*, volume control**, track control*, play/pause music* What's in the box? 1 Jabra Revo headphones, 1 protective bag, 1 detachable 3.5 mm audio cable (1.2 m), 1 quick start guide, 1 Jabra Sound App unique registration leaflet, 1 warranty leaflet, 1 register paper. Certification CE	Microphone frequency range	100Hz - 8kHz
Storage temperature -40° C to 65° C (-40 F to 149 F) Reliability testing Drop tested from 2 m height, fold tested 3500 times, bend tested 10000 times, cable tested to withstand 15 kg pull force, dirt, temperature and humidity tested Jabra Revo materials Silicon, PCM, PC, Zinc, AL, PU, ABS, TPE Features Foldable design, detachable 3.5 mm cable, dual 3.5 mm jack connectors for right or left side use and sharing music, In-line controls for music and calls: answer/end call*, reject call*, voice dialing*, last number redial*, volume control**, track control*, play/pause music* What's in the box? 1 Jabra Revo headphones, 1 protective bag, 1 detachable 3.5 mm audio cable (1.2 m), 1 quick start guide, 1 Jabra Sound App unique registration leaflet, 1 warranty leaflet, 1 register paper. Certification CE	Microphone sensitivity	-42 dB
Reliability testing Drop tested from 2 m height, fold tested 3500 times, bend tested 10000 times, cable tested to withstand 15 kg pull force, dirt, temperature and humidity tested Jabra Revo materials Silicon, PCM, PC, Zinc, AL, PU, ABS, TPE Features Foldable design, detachable 3.5 mm cable, dual 3.5 mm jack connectors for right or left side use and sharing music, In-line controls for music and calls: answer/end call*, reject call*, voice dialing*, last number redial*, volume control**, track control*, play/pause music* What's in the box? 1 Jabra Revo headphones, 1 protective bag, 1 detachable 3.5 mm audio cable (1.2 m), 1 quick start guide, 1 Jabra Sound App unique registration leaflet, 1 warranty leaflet, 1 register paper. Certification CE	Operating temperature	-10° C to 55° C (14 F to 131 F)
withstand 15 kg pull force, dirt, temperature and humidity tested Silicon, PCM, PC, Zinc, AL, PU, ABS, TPE Features Foldable design, detachable 3.5 mm cable, dual 3.5 mm jack connectors for right or left side use and sharing music, In-line controls for music and calls: answer/end call*, reject call*, voice dialing*, last number redial*, volume control**, track control*, play/pause music* What's in the box? 1 Jabra Revo headphones, 1 protective bag, 1 detachable 3.5 mm audio cable (1.2 m), 1 quick start guide, 1 Jabra Sound App unique registration leaflet, 1 warranty leaflet, 1 register paper. Certification CE	Storage temperature	-40° C to 65° C (-40 F to 149 F)
Features Foldable design, detachable 3.5 mm cable, dual 3.5 mm jack connectors for right or left side use and sharing music, In-line controls for music and calls: answer/end call*, reject call*, voice dialing*, last number redial*, volume control**, track control*, play/pause music* What's in the box? 1 Jabra Revo headphones, 1 protective bag, 1 detachable 3.5 mm audio cable (1.2 m), 1 quick start guide, 1 Jabra Sound App unique registration leaflet, 1 warranty leaflet, 1 register paper. Certification CE	Reliability testing	
use and sharing music, In-line controls for music and calls: answer/end call*, reject call*, voice dialing*, last number redial*, volume control**, track control*, play/pause music* What's in the box? 1 Jabra Revo headphones, 1 protective bag, 1 detachable 3.5 mm audio cable (1.2 m), 1 quick start guide, 1 Jabra Sound App unique registration leaflet, 1 warranty leaflet, 1 register paper. Certification CE	Jabra Revo materials	Silicon, PCM, PC, Zinc, AL, PU, ABS, TPE
start guide, 1 Jabra Sound App unique registration leaflet, 1 warranty leaflet, 1 warranty leaflet, 1 register paper. Certification CE	Features	use and sharing music, In-line controls for music and calls: answer/end call*, reject call*, voice
	What's in the box?	start guide, 1 Jabra Sound App unique registration leaflet, 1 warranty leaflet, 1 warning leaflet,
Warranty One-year limited warranty	Certification	CE
	Warranty	One-year limited warranty



